

cables

& accessories guide

Van Domburg Partners continues to work closely with our customers and suppliers to ensure all your needs are met.

We're the one stop cable shop for all your audio, video and data requirements.



For any product enquiries please contact our sales department on +31(0)180 745 888 or email sales@vandomburg.nu

Meet our Sales Team



David van Soest Account Manager david@vandomburg.nu



Enzo Cantini Account Manager enzocantini@vandomburg.nu



Laurens de Baere
Account Manager
laurensdebaere@vandomburg.be



Bob van Holland Internal Sales bobvanholland@vandomburg.nu



Ricardo van Domburg Technical Sales ricardo@vandomburg.nu



Ferry Neervoort Technical Sales ferryneervoort@vandomburg.nu



Simone Oorschot Business Support simone@vandomburg.nu



Eloisa Gerritse

Business Support
eloisagerritse@vandomburg.nu



Svetlana Bouwman
Customer Service
svetlanabouwman@vandomburg.nu

+31 (0) 180 745 888 | sales@vandomburg.nu

Adapter Line by Liberty AV Solutions







The new HDMI AdapterLine makes it easier than ever to connect, takes up less space and keeps your presentation area looking neat and tidy.



New and improved adapter ring system

Features and Benefits

- · New, updated 'line-style' easily tucks away into table boxes. · AdapterLine (tether) is made of durable stainless steel
- · Faster and more convenient to add or remove adapters. Undo one wire end to add/remove adapters. Opposite end has fixed cap.
- · Simple to attach the individual adapters to the HDMI cable head no awkward twisting
- \cdot New die cast aluminium clamp (DL-LN) is smaller and stronger with metal hinge and clasp
- · The clamp and line use the same torx screw as previous adapter rings. No need to have separate allen wrench, saving assembly time.
- US Patent No. 9,784,338 and 10,041,565



DL-AR

This DigitaLinx adapter ring includes:

- · 1 Interseries adapter Micro-HDMI "D" male to HDMI "A" female (ARMDHD)
- · 1 Interseries adapter Mini-HDMI "C" male to HDMI "A" female (ARMCHD)
- · 1 Interseries adapter Mini-DisplayPort male to HDMI female (ARMDPHD)
- · 1 Interseries adapter full sized DisplayPort male to HDMI female (ARDPHD)
- 1 Interseries adapter for DVI Digital male to HDMI female (ARDVHD)
- 1 Base security clamp, cable and hardware for DL-AR system (DL-CL)


Make Liberty's breakthrough DL-AR adapter ring part of every install





This DigitaLinx adapter ring includes:

- 1 Interseries adapter full sized DisplayPort male to HDMI female (ARDPHD)
- 1 Interseries adapter Mini-DisplayPort male to HDMI female (ARMDPHD)
- · 1 Interseries adapter USB-C male to HDMI female (ARUCMHDF)
- · 1 Base security clamp, cable and hardware for DL-AR system (DL-CL)



HDMI female 8 inches long (AR-DPM-HDF)

DigitaLinx adapter ring includes:

- · 1 adapter cable Mini-DisplayPort male to HDMI female 6 inches long (AR-MDPM-HDF)
- · 1 adapter cable USB "C" male to HDMI female 9 inches long (AR-UCM-HDF)
- · 1 Base security clamp, cable and hardware for DL-AR system



DL-AR1883



DL-AR2126

This DigitaLinx adapter ring includes:

- · 1 adapter cable Mini-HDMI "C" male to HDMI female 8 inches long (AR-MCHM-HDF)
- · 1 adapter cable Mini-DisplayPort male to HDMI female 6 inches long (AR-MDPM-HDF)
- · 1 adapter cable USB "C" male to HDMI female 9 inches long (AR-UCM-HDF)
- · 1 Base security clamp, cable and hardware for DL-AR system

DL-AR3979

DL-AR6853

DL-AR4074

DL-AR3950











Code

Security clamp to attach Apple Adapters to DL-AR system

DL-AR2

This DigitaLinx adapter ring includes:

- 1 Interseries adapter Micro-HDMI
 "D" male to HDMI "A" female
 (ARMDHD)
- 1 Interseries adapter Mini-HDMI "C" male to HDMI "A" female (ARMCHD)
- 1 Interseries adapter
 Mini-DisplayPort male to HDMI female (ARMDPHD)
- 1 Interseries adapter full sized DisplayPort male to HDMI female (ARDPHD)
- 1 Base security clamp, cable and hardware for DL-AR system (DL-CL)

DL-AR1200

This DigitaLinx adapter ring includes:

- 1 Interseries adapter Mini-DisplayPort male to HDMI female (ARMDPHD)
- 1 Interseries adapter full sized DisplayPort male to HDMI female (ARDPHD)
- 2 Security clamps to attach Apple adapters to DL-AR system (DL-AP)
- 1 Apple Certified adapter Lightning (M) to HDMI (F) and Lightning (F) to power device (MD826ZM/A)
- 1 Base security clamp, cable and hardware for DL-AR system (DL-CL)

This DigitaLinx adapter ring includes:

 1 Interseries adapter full sized DisplayPort male to HDMI female (ARDPHD)

DL-AR1909

- 1 Interseries adapter Mini-DisplayPort male to HDMI female (ARMDPHD)
- 1 adapter cable USB "C" male to HDMI female 9 inches long (AR-UCM-HDF)
- 1 Base security clamp, cable and hardware for DL-AR system



Code

Base security clamp, cable and hardware for DL-AR system



Code

ARUCMHDF-AD

Adapter USB-C HD 4K black

DL-AR4162

As the DL-AR2 but with 4K DisplayPort (ARDP4KHF) and Mini DP Adapters (ARMDP4KHF)

DL-AR4055

As the DL-AR but with 4K DisplayPort (ARDP4KHF) and Mini DP Adapters (ARMDP4KHF). Only 1 x Security clamp to attach Apple Adapters

DL-AR4131

Same as FFDL-AR1909 but with 4K Display Port Adapter (ARDP4KHF) & 4K Mini-Display-Port Adapter (ARMDP4KHF)



Code

VGA + USB to HDMI adapter



BOYD Connection Hub

The DigitaLinx BYOD-HUB-UT is a 6x1 multi format AV auto switcher and scaler that features a variety of integrated input connection leads. They are compatible with devices such as mobile phones and tablets, allowing a dependable wired connection to a display or TV monitor for presentation purposes.



HDMI Auto Sensing Room Controller



DL-UHDILC

Features and Benefits


- Stand alone unit
- Automates room peripherals when video signal is introduced to system
- Passes HDMI & HDMI 2.0 signals up to 18G 4K60 4:4:4
- Built in CEC controller from HDMI out.
- · Built in RS232 controller to control display device
- Built in RELAY control for room peripherals such as projector screen or window shade
- · De-embeds audio to coax S/PDIF or Stered
- · Switch for EDID Management with 15 EDID presets

The BYOD-HUB-UT features the following AV input leads; (1) Lightning (1) USB-C

(1) Mini-DisplayPort (1) DisplayPort (1) HDMI Type-A and (1) HDMI Type-D. The BYOD-HUB-UT features an HDMI output with a built in 4K video scaler that can be set to either 4K or 1080p.

HDCP Compliant

Code BYODHUBUT



HDMI A male to 270 degree (UP) A male connectivity

Features and Benefits

- ·Black molding and cable · 28 AWG TMDS Pair Construction
- · Dual layer foil and high % braid shielding
- · Flexible polyvinyl chloride jacket · High speed HDMI(R) with Ethernet rated
- ·10.2 Gbps / 4K Video / 3D / CEC / ARC
- · NEC CL2, CEC CMG FT4, RoHS Compliant

Applications

- HDMI digital multimedia device interconnection
- Low profile flat screen connection against a wall
- HDMI port connection in low clearance areas

Code	Length	Colour
RVHDRAU3	0.9m	Black
RVHDRAU6	1.8m	Black
RVHDRAU10	3.0m	Black
RVHDRAU15	4.5m	Black

Premium high speed HDMI cables with Ethernet

- · Full 18 Gig 4K@60Hz and HDR certified by HDMI ATC.
- ·Supports Ethernet, ARC, CEC, and all HDMI audio formats
- NEC CM, CEC CMG FT4, RoHS/REACH compliant
- · Full traceable HDMI premium serialized
- · All 0.9, 1.8, 3, 4.5, 6 and 7.3 metres lengths rated for 18.0 Gbps

Code	Length	Colour
HDPMM03F	0.9m	Black
НДРММ06F	1.8m	Black
HDPMM10F	3.0m	Black
HDPMM15F	4.5m	Black
HDPMM20F	6.0m	Black
HDPMM24F	7.3m	Black

Commercial grade high retention high speed HDMI cables with Ethernet



Features and Benefits

- · High retention gold plated HDMI "A" plugs
- · Fully shielded from connector shroud to shroud
- · All lengths rated for 10.2 Gbps
- · 4K video, Audio Return, Ethernet, CEC
- · 5 meters and longer are active and directiona
- · NEC CL2, CEC CMG FT4, RoHS/REACH Compliant

Applications

- Commercial and residential HDMI connectivity
- 3D, 4K, Deep Color applications and installations
- · Audio Visual equipment hookup and much mor

More lengths ^{available} on request

Code	Length	Colour
E2HDSEMM01	0.98m	Black
E2HDSEMM02	1.98m	

Code	Length	Colour
E2HDSEMM08	8m	Black
E2HDSEMM15	15m	Black



Digitalinx by Liberty AV Solutions

4x1 Multi-format conference room collaboration switcher/extension set

4K 10.2G 2 HDMI & 1 VGA input on TX plus 1 HDMI input on RX switched, extended over HDBaseT, and scaled up to 4K with automated display control.



Code SE3H1VC

Digitalinx 5x1 "Soft Codec" series multi-format table box presentation switcher/extender

4K60 18C 4x1
(Standalone) or 5x1
(When using optional
HDBT RX) table box
presentation switcher
with HDMI & USB-C
inputs, USB3.0 hub,
simple display control
& pass-through power.



Code

SC41UPBXTX







Celerity Technologies Universal DisplayPort AOC

Code
DP4KHDF



4K DisplayPort to HDMI cable adapter

Code DP4KHDF

4K Mini-DisplayPort to HDMI cable adapter

Code
MDP4KHDF



Code	Length	Colour
DPMM010M	10m	Black
DРММ015M		Black
DPMM030M	30m	

- Polymer Ontical Fiber (DOF) for better flexibility
- Ultra-small diameter cable
- Draws power from the DisplayPort receptacle power-pin
- DisplayPort 1.2 or 1.3. HDCP 1.3 or 2.2
- Supports 4K@60Hz with 4:4:4 Chroma Sampling
- 5.4Gbps per channel x 4 channels
- Lengths: 10, 15 and 30 meters
- NEC/CEC rated CMP-OF Plenum, RoHS-2 Compliant





Digitalinx by Liberty AV Solutions

USB 2.0 high speed high performance twisted pair extender set

- · Extends USB high-speed (480 Mbps) up to 100 m (330 ft) & supports isochronous data for use with USB cameras
- · Includes transmitter and receiver
- · Can be powered at either the client or host device
- · Uses any Cat5e/6/6A twisted pair cabling
- · Supplies 500mA to USB devices
- ·Can also be used to extend USB 1.1 signals
- ·Transparent USB; Plug & Play (no software drivers needed)
- ·Compatible with all major operating systems





Code

USB 3.0 fiber optic extender set

- · Active USB 3.0 extension up to 100 meters (OM3 MM) · Supports USB 3.0
- \cdot 2-port hub on client end \cdot Host-side powered via USB port from host PC
- · Includes client-side power supply with locking power connector
- · Transparent USB; Plug & Play (no software drivers needed)
- · Compatible with all major operating systems
- · Not backwards with USB 1.1/2.0. 3.0 Only

Code

IFOUSB3





USB 2.0 high speed high performance extension system w/ 4 port USB hub

- · Extends USB 2.0 High-Speed (480 Mbps) up to 100 m (330 ft
- Powered at the client device
- Four port client side supplies500mA to USB devices
- · Uses any Cat5e/6/6A twisted pair cabling



- Fransparent USB; Plug & Play
- ·Compatible with all major operating systems



Code

DIGIUSB24

USB 3.1 high performance/backward compatible extender set

- · Backward compatible with previous USB versions
- · Multiple version can be running simultaneously
- ·USB 3.1 extension up to 100m over Cat6A/7
- · 4 Port USB hub on client end
- Extend multiple formats at the same time such as 3.0 and
 2.0 devices



Code

NTUSB3.1CX



